

Sony VPLPX11

2000 Ansi Lumens XGA Portable/Installation Projector

The VPLPX11 portable multimedia projector offers an outstanding combination of press-and-play performance and total easy of use. The Component Video allows you to connect to your DVD Player and a video display (analog TV, Digital TV-HDTV set) to project all your favourite movies or TV shows on a 40 to 300 inch screen. With an outstanding brightness of 2000 ANSI lumens and true XGA resolution for brilliant image reproduction, it includes an Off & Go function that allows the cooling fan to operate for a period of time after its power has been switched off. This powerful compact projector is also ideal for A/V presentations, it's flexibility and ease of use makes it beneficial to any office environment.

- The multipurpose projector that can be used as a portable one
- It delivers high brightness of 2000 ANSI lumens and high resolution of true XGA
- It incorporates an extra input-and-output terminal
- An Off & Go function allows the cooling fan to operate for a certain period of time after its power has been switched off
- It can be floor mounted or ceiling mounted
- It provides powerful stereo speakers

***1 ANSI lumens is a measuring method of the American National Standards Institute IT7.228. *2 Projector Station software requirements: Microsoft Windows 98, Windows 98 SE, Windows Me or Windows 2000 operating system.**

Supplied Accessories:

- Remote Commnder (1)
- USB Cable: A type to B type (1)
- CD-ROM (Application Software Projector Station) (1)
- AA size Battery (2)
- Air Filter (1)
- AC Power Cord (1)
- Operation Manual (1)
- Installation Manual for dealers (1)
- Quick Guide (1)

Optional Accessories:

- LMP-P202 Projector Lamp
- VPLL-CT10 Projection Lens
- VPLL-CW10 Projection Lens
- PSS-610//A Suspension Support
- SMF-400 Signal Cable
- SMF-402 Signal Cable

--Optical--

- Projection system: 3 LCD panels, 1 lens projection system
- LCD panel:
 - 0.9-inch p-Si TFT LCD panel with Micro Lens Array
 - 2,359,296 pixels (786,432 pixels x 3)
- Projection lens: 1.3 times manual zoom lens, F1.7 to 2.1, f33.6 to 42 mm
- Lamp: 200 W UHP lamp
- Screen coverage: 40 to 300 inches (viewable area, measured diagonally)

- Light output: 2000 ANSI lumens

--Signals--

- Color system: NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
- Resolution: VIDEO: 750 TV lines, RGB: 1024 x 768 pixels
- Acceptable signals: RGB (fH: 19 to 92 kHz, fV: 48 to 92 Hz), 15 kHz component 50/60 Hz system, composite video, Y/C video

--General--

- Cabinet color: Silky silver
- Speaker: Max. 2 W x 2 (stereo)
- Power requirements: AC 100 to 240 V, 50/60 Hz
- Power consumption: Max. 290 W, Standby 4.2 W
- Operating temperature: 0 to 35 °C (32 to 95 °F)
- Operating humidity: 35 to 85 %
- Dimensions*: 325 (W) x 110 (H) x 285 (D) mm (12 7/8 x 4 3/8 x 11 1/4 inches)
- Mass: Approx. 4.9 kg (10 lb 13 oz)
- Heat dissipation: 989.6 BTU

--Inputs/outputs--

- VIDEO IN
 - Composite: Phono, 1.0 Vp-p \pm 2 dB, sync negative, 75 Ω
 - Y/C IN: Mini DIN 4-pin
 - Y: 1.0 Vp-p \pm 2 dB, sync negative, 75 Ω
 - C:
 - Burst 0.286 Vp-p \pm 2 dB (NTSC), 75 Ω or 0.3 Vp-p \pm 2 dB (PAL), 75 Ω
- AUDIO IN
 - Stereo mini jack, 500 mV rms, impedance more than 47 k Ω
- INPUT A :
 - Analog RGB/Component: HD D-sub 15-pin (female)
 - R/R-Y: 0.7 Vp-p \pm 2 dB, positive, 75 Ω
 - G: 0.7 Vp-p \pm 2 dB, positive, 75 Ω
 - G with Sync/Y: 1.0 Vp-p \pm 2 dB, sync negative, 75 Ω
 - B/B-Y: 0.7 Vp-p \pm 2 dB, positive, 75 Ω
 - SYNC/HD
 - Composite sync: 1.0 to 5.0 Vp-p, high impedance positive/negative
 - Horizontal sync: 1.0 to 5.0 Vp-p, high impedance positive/negative
 - VD
 - Vertical sync: 1.0 to 5.0 Vp-p, high impedance positive/negative
 - AUDIO IN: Stereo mini jack, 500 mV rms, impedance more than 47 k Ω
- INPUT B :
 - Analog RGB/Component: HD D-sub 15-pin (female)
 - R/R-Y: 0.7 Vp-p \pm 2 dB, positive, 75 Ω
 - G: 0.7 Vp-p \pm 2 dB, positive, 75 Ω
 - G with Sync/Y: 1.0 Vp-p \pm 2 dB, sync negative, 75 Ω
 - B/B-Y: 0.7 Vp-p \pm 2 dB, positive, 75 Ω
 - SYNC/HD
 - Composite sync: 1.0 to 5.0 Vp-p, high impedance positive/negative
 - Horizontal sync: 1.0 to 5.0 Vp-p, high impedance positive/negative
 - VD
 - Vertical sync: 1.0 to 5.0 Vp-p, high impedance positive/negative
 - AUDIO IN: Stereo mini jack, 500 mV rms, impedance more than 47 k Ω
- USB : Up (B type female) x 1
- OUTPUT :
 - Analog RGB/Component: HD D-sub 15-pin (female)
 - R/R-Y,G/Y,B/B-Y: Gain unity, 75 Ω
 - SYNC/HD, VD

4.0 Vp-p(open), 1.0 Vp-p, 75 Ω
AUDIO(variable out)
Stereo mini jack, max 1 Vrms, when an output signal is 500 mV rms, impedance more than 5 khms
REMOTE : RS-232C
D-sub 9-pin (female)

--Safety regulations--

- UL, cUL, DHHS, DNHW, DENAN, FCC class A, NEMKO, CE (LVD, EMC), C-Tick, VCCI, JEITA

*** Excluding all protruding parts.**